

METHOD OF PRODUCING AN LED ROPE LIGHT

FIELD OF THE INVENTION

5 The present invention relates to a method of quickly producing a light-emitting-diode (LED) rope light, and more particularly to a method of producing an LED rope light at largely reduced manufacturing cost and shortened time.

10

BACKGROUND OF THE INVENTION

A conventional rope light includes a plurality of bulbs as its light sources. These bulbs are serially
15 connected to one another to form one or two bulb strings, which are then set in a long core tube. The core tube is cut at an outer surface to provide a longitudinal opening, via which the bulb string or strings are positioned into the core tube. Two power cords having
20 different polarities are embedded in two opposite sides of a wall of the core tube. The two embedded power cords are cut at staggered positions to expose bare wires, to which lead wires of the first and the last bulb in the bulb strings are separately electrically connected
25 to emit light. The core tube with bulbs is then drawn into a transparent outer tube to complete a conventional

rope light. In the case two bulb strings are formed, lead wires of the bulbs must be covered with insulated sleeves to avoid a short circuit.

5 In the above-described conventional rope light, the bulbs are horizontally set into the core tube via the longitudinal opening provided on one side of the core tube. The existence of the longitudinal opening largely reduces an overall structural strength of the
10 core tube. When the rope light is used on a stage or at places close to steps and tends to be twisted, deformed, trodden or impacted, the core tube with reduced structural strength is not strong enough to bear such external forces, resulting in damaged bulbs in the core
15 tube. Moreover, it is difficult and requires increased material and labor costs to mount the insulated sleeves around the lead wires of two adjacent bulb strings that are set in the core tube at the same time. The conventional rope light with two bulb strings therefore
20 requires increased material cost and is not easy to assemble.

Another problem with the conventional rope light is that the bulbs consume high power and generate a large
25 amount of heat to cause deteriorated core tube and outer tube of the rope light. Broken bulbs in the

deteriorated core tube and outer tube tend to cause short circuit, and the conventional rope light is therefore not safe for use.

5 It is therefore tried by the inventor to develop a method of producing an energy saving, safe, and environment friendly LED rope light at reduced cost and shortened assembling time to eliminate the problems existed in the conventional rope light.

10

SUMMARY OF THE INVENTION

A primary object of the present invention is to provide a method that enables production of an energy saving, safe, and environment friendly LED rope light at reduced
15 cost and shortened assembling time.

To achieve the above and other objects, the method of the present invention for producing an LED rope light
20 includes the steps of preparing a plurality of light seats defining a recess therein and a plurality of metal wires having two conductive plates connected to two ends thereof; positioning two conductive plates from two different metal wires in each light seat; processing
25 the light seats to provide light-emitting diodes (LED); serially connecting the light seats to provide an LED

light string; positioning the LED light string into
a hollow power cord holder with the metal wires of the
LED light string correspondingly connected to positive
and negative electrodes of two power cords embedded
5 in the power cord holder; and quickly enclosing said
power cord holder with a transparent outer tube by way
of injection molding to form an LED rope light.

BRIEF DESCRIPTION OF THE DRAWINGS

10

The structure and the technical means adopted by the
present invention to achieve the above and other objects
can be best understood by referring to the following
detailed description of the preferred embodiments and
15 the accompanying drawings, wherein

Fig. 1 illustrates the first step of the method of the
present invention for producing an LED rope light;

20 Fig. 2 is similar to Fig. 1 but shows that a differently
shaped conductive plate is used to produce the LED rope
light;

Fig. 3 illustrates the second step of the method of
25 the present invention for producing an LED rope light;

Fig. 4 illustrates the third step of the method of the present invention for producing an LED rope light;

Fig. 5 illustrates the fourth step of the method of the present invention for producing an LED rope light;

Fig. 6 illustrates the fifth step of the method of the present invention for producing an LED rope light;

Fig. 7 illustrates the sixth step of the method of the present invention for producing an LED rope light;

Fig. 8 illustrates a finished product of the LED rope light produced with the method of the present invention;

Fig. 9 is similar to Fig. 7 but shows that a differently sectioned outer tube is used to produce the LED rope light;

Fig. 10 illustrates another finished product of the LED rope light produced with the method of the present invention;

Fig. 11 illustrates a differently structured power cord holder for use in the fifth step of the method of the present invention for producing an LED rope light;

Fig. 12 illustrates a further outer tube having a cross section corresponding to that of the power cord holder of Fig. 11 for producing the LED rope light of the present invention; and

Fig. 13 illustrates another finished product of the LED rope light produced with the method of the present invention and using the power cord holder and the outer tube shown in Figs. 11 and 12, respectively.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Please refer to Figs. 1 to 7, in which different steps included in the method of the present invention for producing an LED light rope are illustrated.

In the first step of the method of the present invention as shown in Fig. 1, a plurality of metal wires 1 having two rectangular conductive plates 11 connected to two ends thereof are prepared. Each of the conductive plates 11 is provided at two lateral sides with two oppositely projected teeth 12. There is also prepared a plurality of open-topped light seats 2, each of which defines a recess 21 therein. Each of the light seats 2 is provided at two transverse ends with two opposite

and symmetrical notches 22. It is to be noted that the
conductive plate 1 is not restricted to a rectangular
plate but may be a trapezoidal plate having a shorter
inner transverse end and a longer outer transverse end,
5 as shown in Fig. 2.

In the second step of the method of the present invention
as shown in Fig. 3, the metal wires 1 are assembled
to the light seats 2, so that each light seat 2 has
10 two metal wires 1 separately extended through the two
notches 22 on the light seat 2 with one conductive plate
11 from each metal wire 1 fitly located in the recess
21 defined by the light seat 2. It is to be noted that
the two conductive plates 11 located in the same one
15 recess 21 do not contact with each other, and the two
laterally projected teeth 12 on each conductive plate
11 are pressed against inner surfaces of two
longitudinal sides of the recess 21 to thereby firmly
hold the conductive plate 11 in place in the recess
20 21.

In the third step of the method of the present invention
as shown in Fig. 4, an LED chip 3 is firmly attached
to one of the two conductive plates 11 in the recess
25 21 of each light seat 2 by means of a bonding agent,
and then a metal conductor 4 is connected at positive

and negative electrodes to the LED chip 3 and the other
conductive plate 11 in the recess 21, respectively,
with the help of a microscope, so that the a plurality
of light seats 2 are electrically serially connected
5 at a positive electrode of a first one to a negative
electrode of a next one to provide a light string.

In the fourth step of the method of the present invention
as shown in Fig. 5, the light seats 2 in each light
10 string are separately positioned in forming molds (not
shown) and sent into an encapsulating compound injector
(not shown) for encapsulation. The forming molds with
the light seats 2 and injected encapsulating compound
are then sent into a drying oven (not shown), so that
15 the encapsulating compound is set to form a mask 5 over
each LED chip 3, and an LED light string 6 is obtained.

In the fifth step of the method of the present invention
as shown in Fig. 6, a hollow power cord holder 7 is
20 prepared. The power cord holder 7 is cut at a top thereof
to provide a V-sectioned opening, via which the light
seats 2 may be implanted into an internal space of the
hollow power cord holder 7. Inner and outer bottom
surfaces of the power cord holder 7 opposite to the
25 V-sectioned opening are formed into a flat surface and
a convex surface 72, respectively. Two power cords 71

having two different polarities are separately embedded in two sidewall portions of the power cord holder 7. When the LED light string 6 formed from the light seats 2 is implanted into the inner space of the power cord holder 7, positive and negative electrodes at two outmost ends of the LED light string 6 are separately connected to the positive and the negative power cord 71, respectively.

10 In the sixth and final step of the method of the present invention as shown in Fig. 7, the power cord holder 7 along with the LED light string 6 implanted therein are positioned into an injection-molding machine (not shown), so that the power cord holder 7 with implanted
15 LED light string 6 is quickly enclosed in a transparent outer tube 8 to form an LED rope light 9. Then, a connector 91 for connecting to a power source is connected to an end of the LED rope light 9, as shown in Fig. 8.

20 It is to be noted that the transparent outer tube 8 of the LED rope light 9 is not necessarily a round-sectioned tube as shown in Figs. 7 and 8, but may have other different cross sections depending on
25 actual needs. For example, the transparent outer tube 8 may have a rectangular cross section when it is drawn

from the injection-molding machine, as shown in Fig. 9. In this case, the power cord holder 7 may have flat upper and lower outer surfaces and two convex side surfaces to correspond to the rectangular cross section of the transparent outer tube 8. Moreover, to enable the rectangular-sectioned LED rope light 9 to be highly flexible and bendable, the rectangular-sectioned transparent outer tube 8 is provided on outer surfaces with a plurality of circles of axially equally spaced grooves 81, as shown in Fig. 10.

Alternatively, as can be seen from Figs. 11 and 12, the power cord holder 7 prepared in the fifth step may be in the form of a long strip, on which a plurality of through holes 73 are equally spaced for the light seats 2 on the LED light string 6 to separately locate therein; and the transparent outer tube 8 produced in the sixth step may be a substantially rectangular-sectioned tube having a convex top 81, a flat bottom, and two flat sidewalls, and defining a rectangular-sectioned inner space for drawing the strip-like power cord holder 7 into the outer tube 8 to produce a finished product of the LED rope light 9 shown in Fig. 13.

25

With the method of the present invention, the LED rope

light 9 may be produced at a largely reduced amount
of raw material. The LED chips 3 of the LED rope light
9 formed with the method of the present invention are
serially connected at a positive electrode of a first
5 one and a negative electrode of a next one, and may
be tested immediately after the application of the
encapsulating compound. In the event the LED light
string 6 is tested and proven as a good one, it is then
assembled to the power cord holder 7. After the power
10 cord holder 7 with the light string 6 assembled thereto
is sent to an injection-molding machine for enclosing
with the transparent outer tube 8, a finished product
of the LED rope light may be obtained after the connector
91 is connected to an end thereof. In this manner, it
15 is not necessary to troublesomely check the LED chips
one by one while an energy-saving, environment-friendly,
and safe LED rope light may be produced with simplified
procedures, reduced loss of raw material, and shortened
assembling time.

20